## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization

International Bureau



# 

### (43) International Publication Date 1 April 2004 (01.04.2004)

## (10) International Publication Number WO 2004/026500 A3

(51) International Patent Classification7: 43/10

E21B 23/00.

(21) International Application Number:

PCT/US2003/025675

(22) International Filing Date: 18 August 2003 (18.08.2003)

(25) Filing Language:

linglish

(26) Publication Language:

Linglish

(30) Priority Data: 60/412,544

20 September 2002 (20.09.2002) US

(71) Applicant (for all designated States except US): ENVEN-TURE GLOBAL TECHNOLOGY [US/US]: 16200 A. Park Row, Houston, TX 77084 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): SHUSTER, Mark

[US/US]: 19115 Prospect Ridge Lane, Houston, TX 77094 (US). RING, Lev [US/US]: 14126 Heatherhill Place, Houston, TX 77077 (US).

- (74) Agent: MATTINGLY, Todd; Haynes and Boone, LLP, Suite 3100, 901 Main Street, Dallas, TX 75202 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FL GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC. LK, LR, LS, LT, LU, LV, MA, MD. MG, MK, MN. MW. MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE. SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ. VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FL FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: SELF-LUBRICATING EXPANSION MANDREL FOR EXPANDABLE TUBULAR



(57) Abstract: A self-lubricating expansion mandrel (205) includes a system for lubricating the interface between the self-lubricating expansion mandrel (205) and a tubular member (210) during the radial expansion of the tubular member (210).

#### WO 2004/026500 A3

SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, Cl, CM, (88) Date of publication of the international search report: GA. GN, GQ, GW, ML, MR, NE, SN, TD, TG).

### Declaration under Rule 4.17:

of inventorship (Rule 4.17(iv)) for US only

#### Published:

- with international search report

13 January 2005

(15) Information about Correction: **Previous Correction:** see PCT Gazette No. 43/2004 of 21 October 2004, Sec-

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/25675

A. CLASSIFICATION OF SUBJECT MATTER  IPC(7) : E21B 23/00, 43/10					
US CL : 166/207, 55.7					
According to International Patent Classification (IPC) or to both national classification and IPC					
B. FIELDS SEARCHED					
Minimum do	cumentation searched (classification system follower	by classification symbols)			
Minimum documentation searched (classification system followed by classification symbols) U.S.: 166/207, 55.7, 50, 55, 55.1, 205, 209, 216, 242.1, 297, 380, 384					
0.0	27, 300, 34				
Documentati	on searched other than minimum documentation to the	e extent that such documents	are included in the fields searched		
Electronic da	ata base consulted during the international search (na	ne of data base and, where pr	acticable, search terms used)		
Please See C	ontinuation Sheet	•	,		
I					
C. DOCUMENTS CONSIDERED TO BE RELEVANT					
Category *	Citation of document, with indication, where a	opropriate, of the relevant pas	sages Relevant to claim No.		
X	US 2002/0062956 A1 (MURRAY et al.) 30 May 20				
	the second secon	702 (30.3.2002), WILDIE GOEGI	1-9		
Y			10-23		
			.0.20		
Y	US 5,014,779 A (MELING et al) 14 May 1991 (14	.05, 1991), column 3, lines 31	-36 19-23		
			""		
Y	US 4,526,839 A(HERMAN et al) 2 July 1985 (02.6	7.1985), column 5, line 60- c	column 6, 10-18, 23		
	line 16.				
Α	US 6,325,148 B1 (TRAHAN et al) 4 December 200	1, (04.12.2001), whole docu	ment 1-23		
			į		
A	US 3,203,451 A(VINCENT) 31 August 1965 (31.08.1965), whole document.				
A	US 6,158,963 A (HOLLIS et al) 12 December 2000 (12.12.2000), whole document.		ent. 1-23		
i			1		
A	US 4,505,987 A (YAMADA et al.) 19 March 1985 (19.03.1985), whole document.		nt. 1-23		
			l		
-			İ		
			1		
		<u> </u>			
Further	documents are listed in the continuation of Box C.	See patent family a	nnex.		
Special categories of cited documents:     T later document published after the international filing date or priority					
	-	date and not in conflict	with the application but cited to understand the		
	defining the general state of the art which is not considered to be lar relevance	principle or theory unde	criying the invention		
-			relevance; the claimed invention cannot be		
"E" earlier ap	plication or patent published on or after the international filing date	considered novel or can when the document is to	not be considered to involve an inventive step		
"L" document	which may throw doubts on priority claim(s) or which is cited to				
establish t specified)	he publication date of another citation or other special reason (as		relevance; the claimed invention cannot be a inventive step when the document is		
• •		combined with one or m	tore other such documents, such combination		
"O" document	referring to an oral disclosure, use, exhibition or other means	being obvious to a perso	on skilled in the art		
"P" document published prior to the international filing date but later than the "&" document member of the same potent family					
priority date claimed					
Date of the actual completion of the international search  Date of mailing of the international search report					
		<b>.</b>	25 MAY 2004		
11 Determoti 2003 (11.12.2003)					
	ailing address of the ISA/US	Apportized officer			
	I Stop PCT, Attn: ISA/US	David J. Baxaeli			
	nnissioner for Patents . Box 1450	~//			
Ale	kandria, Virginia 22313-1450	Telephone No. (703) 308-1	113		
Facsimile No	Facsimile No. (703) 305-3230				
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				

Form PCT/ISA/210 (second sheet) (July 1998)

	PCT/US03/25675
INTERNATIONAL SEARCH REPORT	
•	
	·
The second of th	
Continuation of B. FIELDS SEARCHED Item 3: JPO, EPO, Derwent	
	:
Terms: swedge/swage, lubricate/lubricant, teflon, friction, coating,	
•	
Form PCT/ISA/210 (second sheet) (July 1998)	

# (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization

International Bureau



# 

(43) International Publication Date 1 April 2004 (01.04.2004)

**PCT** 

(10) International Publication Number WO 2004/026500 A3

(51) International Patent Classification<sup>7</sup>: E2 43/10

E21B 23/00,

(21) International Application Number:

PCT/US2003/025675

(22) International Filing Date: 18 August 2003 (18.08.2003)

(25) Filing Language:

English

(26) Publication Language:

linglish

(30) Priority Data:

60/412.544

20 September 2002 (20.09,2002) US

(71) Applicant (for all designated States except US): ENVENTURE GLOBAL TECHNOLOGY [US/US]; 16200 A. Park Row, Houston, TX 77084 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): SHUSTER, Mark

[US/US]; 19115 Prospect Ridge Lane, Houston, TX 77094 (US). RING, Lev [US/US]; 14126 Heatherhill Place, Houston, TX 77077 (US).

- (74) Agent: MATTINGLY, Todd: Haynes and Boone, LLP. Suite 3100, 901 Main Street, Dallas, TX 75202 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH. GM, KE, LS, MW. MZ. SD, SL, SZ, TZ, UG. ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: SELF-LUBRICATING EXPANSION MANDREL FOR EXPANDABLE TUBULAR



(57) Abstract: A self-lubricating expansion mandrel (205) includes a system for lubricating the interface between the self-lubricating expansion mandrel (205) and a tubular member (210) during the radial expansion of the tubular member (210).

#### 

SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM. Date of publ. GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

## Published:

- with international search report
- with amended claims

(88) Date of publication of the international search report: 13 January 2005

Date of public of the amended claims: 24 February 2005

(15) Informat. about Correction:
Previous Correction:

see PCT Gazette No. 43/2004 of 21 October 2004, Section  $\Pi$ 

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

### AMENDED CLAIMS

[received by the International Bureau on 23 July 2004 (23.07.2004); claims 24-47 added

- 17. The self-lubricating expansion mandrel of claim 12, wherein the solid lubricant retained in the plurality of troughs formed in a textured pattern comprises a thermo-sprayed coating.
- 18. The self-lubricating expansion mandrel of claim 12, wherein the depth of the plurality of troughs formed in a textured pattern is in a range of between about 50 and 150 microns.
- 19. A self-lubricating expansion mandrel for expanding a tubular member, comprising:
  - a housing including a tapered outer surface;
  - one or more grooves formed in the tapered outer surface; and
  - a grease supply chamber in the housing;
  - a conduit from the grease supply chamber to one or more of the grooves; and
- means for forcing grease from the grease supply chamber trough the conduit to one or more of the grooves.
- 20. The self-lubricating expansion mandrel of claim 19, wherein the one or more grooves comprise circumferential grooves.
- 21. The self-lubricating expansion mandrel of claim 19, wherein the grooves comprise axial grooves.
- 22. The self-lubricating expansion mandrel of claim 19, wherein the grooves comprise a pattern of grooves with both an axial and a circumferential component.
- 23. The self-lubricating expansion mandrel of claim 22, wherein the pattern of grooves comprises a textured surface.
- 24. A self-lubricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and solid lubricant retained in one or more of the grooves; wherein the grooves comprise circumferential grooves.
- 25. A self-lubricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and solid lubricant retained in one or more of the grooves; wherein the grooves comprise axial grooves.
- 26. A self-lubricating expansion mandrel for expanding a tubular member, comprising:
  a housing including a tapered outer surface;
  one or more grooves formed in the tapered outer surface; and
  solid lubricant retained in one or more of the grooves;
  wherein the grooves comprise a pattern of grooves with both an axial and a circumferential component.
- 27. A self-lubricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and

WO 2004/026500 PCT/US2003/025675

solid lubricant retained in one or more of the grooves; wherein the pattern of grooves comprises a textured surface.

- 28. A self-hibricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and solid lubricant retained in one or more of the grooves; wherein the depth of the grooves is in a range of between about 1 and 4 microns.
- 29. A self-lubricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and solid lubricant retained in one or more of the grooves; wherein the depth of the grooves is in a range of between about 10 and 50 microns.
- 30. A self-lubricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and solid lubricant retained in one or more of the grooves; wherein the solid lubricant retained in one or more of the grooves comprises a thermo-sprayed coating.
- 31. A self-lubricating expansion mandrel for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more grooves formed in the tapered outer surface; and solid lubricant retained in one or more of the grooves; wherein the depth of the grooves is in a range of between about 50 and 150 microns.

32.

- A self-lubricating expansion device for expanding a tubular member, comprising: a housing including a tapered outer surface; one or more depressions formed in the tapered outer surface; and a lubricant supply chamber in the housing; a conduit from the lubricant supply chamber to one or more of the depressions; and means for forcing lubricant from the lubricant supply chamber trough the conduit to one or more of the depressions.
- 33. The self-hibricating expansion mandrel of claim 32, wherein the one or more depressions comprise circumferential grooves.
- The self-lubricating expansion mandrel of claim 32, wherein the depressions comprise axial 34. grooves.
- 35. The self-lubricating expansion mandrel of claim 32, wherein the depressions comprise a pattern of grooves with both an axial and a circumferential component.

WO 2004/026500 PCT/US2003/025675

36. The self-lubricating expansion mandrel of claim 35, wherein the pattern of grooves comprises a textured surface.

- 37. A self-lubricating expansion device for expanding a tubular member, wherein the interface between the expansion device and the tubular member, during the expansion process, includes a leading edge portion and a trailing edge portion, comprising:
- a housing including a tapered outer surface;
- one or more first depressions formed in the leading edge portion of the tapered outer surface; and a lubricant supply chamber in the housing;
- a conduit from the lubricant supply chamber to one or more of the first depressions;

means for forcing lubricant from the lubricant supply chamber trough the conduit to one or more of the depressions;

one or more second depressions formed in the trailing edge portion of the tapered outer surface; and a solid lubricant provided within one or more of the second depressions.

- 38. The self-lubricating expansion mandrel of claim 37, wherein one or more of the first and second depressions comprise circumferential grooves.
- 39. The self-lubricating expansion mandrel of claim 37, wherein one or more of the first and second depressions comprise axial grooves.
- 40. The self-lubricating expansion mandrel of claim 37, wherein one or more of the first and second depressions comprise a pattern of grooves with both an axial and a circumferential component.
- 41. The self-lubricating expansion mandrel of claim 40, wherein the pattern of grooves comprises a textured surface.
- 42. A method of lubricating the interface between and expansion device and a tubular member during an expansion of the tubular member using the expansion device, wherein the interface between the expansion device and the tubular member comprises a leading edge portion and a trailing edge portion, comprising:

injecting a fluid lubricant into the leading edge portion; and providing a solid lubricant in the trailing edge portion.

43. A system for lubricating the interface between and expansion device and a tubular member during an expansion of the tubular member using the expansion device, wherein the interface between the expansion device and the tubular member comprises a leading edge portion and a trailing edge portion, comprising:

means for injecting a fluid lubricant into the leading edge portion; and means for providing a solid hibricant in the trailing edge portion.

44. A method of lubricating the interface between and expansion device and a tubular member during an expansion of the tubular member using the expansion device, wherein the interface between the

WO 2004/026500 PCT/US2003/025675

expansion device and the tubular member comprises a leading edf portion and a trailing edge portion, comprising:

providing a supply of a fluid lubricant within the expansion device; and injecting the fluid lubricant into the leading edge portion.

45. A system for lubricating the interface between and expansion device and a tubular member during an expansion of the tubular member using the expansion device, wherein the interface between the expansion device and the tubular member comprises a leading edge portion and a trailing edge portion, comprising:

means for providing a supply of a fluid lubricant within the expansion device; and means for injecting the fluid lubricant into the leading edge portion.

46. A method of lubricating the interface between and expansion device and a tubular member during an expansion of the tubular member using the expansion device, wherein the interface between the expansion device and the tubular member comprises a leading edge portion and a trailing edge portion, comprising:

providing a supply of a solid lubricant on the expansion device within the trailing edge portion.

47. A system for lubricating the interface between and expansion device and a tubular member during an expansion of the tubular member using the expansion device, wherein the interface between the expansion device and the tubular member comprises a leading edge portion and a trailing edge portion, comprising:

means for providing a supply of a solid lubricant on the expansion device within the trailing edge portion.